

SF-1000B

Perforated Flat Top

.75" Pitch

Direct Replacement for:
Uni Chain Light 10%

*Non-headed Rods



| Pitch | Thickness | Min Width | Rod | Open Area | Flights | Side Guards |
|-------|-----------|-----------|-------|-----------|---------|-------------|
| .75" | .334" | 6" | .236" | 27% | Yes | Yes |
| 19mm | 8.5mm | 152mm | 6mm | | | |

| Belt Material | Standard Rod Material | Belt Strength | | Temperature Fahrenheit | | Belt Weight Lb/Ft ² | Colors |
|---------------|-----------------------|----------------|--------------|------------------------|------|--------------------------------|---------|
| | | Straight Lb/Ft | Curved Lb/Ft | Min | Max | | |
| PP | PP | 953 | - | 33° | 230° | .96 | W, G, B |
| PE | PE | 812 | - | -76° | 140° | 1 | N, B |
| Acetal | PE | 1360 | - | -50° | 180° | 1.33 | W, B |
| Nylon | PE | 1007 | - | 33° | 356° | 1.02 | BR |

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

| # of Teeth | PD | Bore Size |
|------------|-------|------------|
| 7 | 1.67" | 1"R |
| 10 | 2.40" | 1"R |
| 17 | 4.07" | 1"R, 1.5"S |
| 24 | 5.73" | 1"R, 1.5"S |

Special Order Sprockets Available

| | |
|---------------------------|----------|
| Belt Standard Alterations | +/- .72" |
| Flight Standard Indent | +/- 1.5" |



SAFARI Belting Systems, Inc.
Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com