

SF-1100BNEL

Standard Duty Grip Top

.6" Pitch

Direct Replacement for:
Intralox 1100
Flush Grid Friction Top

*Non-headed Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
.6"	.429"	8.14"	.196"	28%	Yes	No
15.2mm	10.9mm	207mm	5mm			

Belt Material	Standard Rod	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft ²²	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
PP	PP	699	-	33°	150°	1.23	W, G, B

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

# of Teeth	PD	Bore Size
12	2.28"	1"R
16	3.07"	1"R, 1.5"S
24	4.65"	1"R, 1.5"S
32	6.22"	1"R, 1.5"S
18-2R	3.48"	1.5"S
20-2R	3.45"	1.5"S
26-2R	5.06"	1.5"S
32-2R	6.18"	1.5"S

Special Order Sprockets Available

Belt Standard Alterations	+/- 1"
Flight Standard Indent	+/- 2"



SAFARI Belting Systems, Inc.

Conveying Innovation to Industry