


SF-125B

Standard Duty Flush Grid

1" Pitch

Replaces:
 Intralox 900
 Flush Grid (same sprockets)

*Non-headed Rods



Cling-Free Flights
Up to 4" Tall

Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
1.07"	.344"	2"	.18"	38%	Yes	No
27.2mm	8.7mm	51mm	4.5mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft ²	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
PP	PP	710	-	33°	230°	.81	W, G, B
PE	POM	360	-	-76°	140°	.983	N, B
POM	POM	1010	-	-50°	150°	1.27	W, B
ULTRA-TUFF™	POM	999	-	30	302	1.26	N, W, DB
ULTRA-TUFF XMD™	POM	999	-	30	302	1.40	RB

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

# of Teeth	PD	Bore Size
6	2.1"	1"R, 1"S
9	3.1"	1"R, 1.5"S
10	8.2"	1"R, 1.5"S
12	4.1"	1"R, 1.5"S
18	6.1"	1.5", 2.5"S
20-split	6.8"	2.5"S
24	8.2"	1.5"S

Special Order Sprockets Available

Belt Standard Alterations	+/- .33"
Flight Standard Indent	+/- 1.5" No Indent



SAFARI Belting Systems, Inc.
 Conveying Innovation to Industry