

SF-150A

Standard Duty Flat Top

1" Pitch

Direct Replacement for:
Intralox 1600 & 1650
Flat Top


*Non-headed Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
1"	.4"	4"	.20"	0%	Yes	No
25.4mm	10mm	101.6mm	5.2mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft ²	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
PP	PP	735	-	33°	230°	1.06	W, G, B
PE	PE	360	-	-76°	140°	1.10	N, B
POM	PE	1021	-	-50°	150°	1.59	N, B
Ultra Tuff™	POM	940	-	30	302	1.55	N, W, DB
Ultra-Tuff XMD™	POM	940	-	30	302	1.75	RB

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

		
# of Teeth	PD	Bore Size
6	2"	1"R
8	2.5"	1"R
10	3.2"	1.5"S
12	3.9"	1.5"S
16	5.1"	1"R, 1.5"S
20	6.4"	1"R, 1.5"S

Special Order Sprockets Available

Belt Standard Alterations	+/- 1.5"
Flight Standard Indent	+/- .5"



SAFARI Belting Systems, Inc.
Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com