


SF-225BN

Heavy Duty Perforated Flat Top 2" Pitch

Direct Replacement for:
Intralox 800 Series
Perforated Flat Top


*Non-Headed Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
2"	.625"	4"	.265"	18%	Yes	No
50.8mm	15.9mm	101.6mm	6.5mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft ²	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
PP	PP	900	-	33°	230°	1.77	W, G, B
PE	PE	860	-	-76°	140°	1.87	N, B
Acetal	PE	1200	-	-50°	150°	2.60	N, DB
Nylon	PA	1021	-	30°	356°	2.42	BR
ULTIG	POM	1200	-	30°	302°	2.57	B, N, W

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

		
# of Teeth	PD	Bore Size
6	3.8"	1"R, 1.5"S
8	5.1"	1"R, 1.5"S
10	6.5"	1.5", 2.5"S
12	7.7"	1.5", 2.5"S
16	10.3"	1.5", 2.5"S

Special Order Sprockets Available

Belt Standard Alterations	+/- .65" (Depends on Material)
Flight Standard Indent	+/- 1.5"



SAFARI Belting Systems, Inc.

Conveying Innovation to Industry