

SF-2250DN

Heavy Duty Perforated Dimple Top 2" Pitch

Direct Replacement for:
Intralox 800 Series
Perforated Flat Top
Round Hole 11/32"

*Non-headed Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
2"	.725"	4"	.24"	14%	Yes	No
50.8mm	18.4mm	101.6mm	6.1mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature		Belt Weight Lb/Ft ²	Colors
		Straight Lb/Ft	Curved Lb/Ft	Fahrenheit Min	Fahrenheit Max		
PP	PP	900	-	33°	230°	1.55	W, G, B
PE	PE	860	-	-50°	150°	1.60	N, B
Acetal	PE	1200	-	-50°	150°	2.40	N, DB
Ultra Tuff™	POM	1188	-	30°	302°	2.37	N, W, DB
Ultra Tuff XMD™	POM	1188	-	30°	302°	2.64	RB

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN



# of Teeth	PD	Bore Size
6	4"	1" r, 1.5"s
8	5.2"	1.5" s
10	6.5"	1.5", 2.5"s
12	7.7"	1.5", 2.5" s
16	10.3"	1.5", 2.5"s

Special Order Sprockets Available



SAFARI Belting Systems, Inc.

Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com