

SF-250A

Heavy Duty Flat Top

2.5" Pitch

Replaces:
Intralox 1800
Flat Top


*Non-headed Rods



| Pitch | Thickness | Min Width | Rod | Open Area | Flights | Side Guards |
|--------|-----------|-----------|-------|-----------|---------|-------------|
| 2.5" | .725" | 4" | .312" | 0% | Yes | No |
| 63.5mm | 18.42mm | 101.6mm | 7.9mm | | | |

| Belt Material | Standard Rod Material | Belt Strength | | Temperature Fahrenheit | | Belt Weight Lb/Ft ² | Colors |
|-----------------|-----------------------|----------------|--------------|------------------------|------|--------------------------------|----------|
| | | Straight Lb/Ft | Curved Lb/Ft | Min | Max | | |
| PE | PE | 710 | - | -76° | 140° | 2.25 | N, B |
| Acetal | PE | 1490 | - | -50° | 150° | 3.34 | N, DB |
| Ultra Tuff™ | PE | 1386 | - | 30° | 302° | 3.36 | N, W, DB |
| Ultra Tuff XMD™ | PE | 1386 | - | 30° | 302° | 3.70 | RB |

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

|  | | |
|---|-------|-------------|
| # of Teeth | PD | Bore Size |
| 6 | 5" | 1.5"S |
| 8 | 6.5" | 1.5", 2.5"S |
| 10 | 8.1" | 1.5", 2.5"S |
| 13 | 10.5" | 1.5", 2.5"S |

Special Order Sprockets Available

| | |
|---------------------------|----------|
| Belt Standard Alterations | +/- 1" |
| Flight Standard Indent | +/- 1.5" |



SAFARI Belting Systems, Inc.
Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com