

SF-250A

Heavy Duty Flat Top

2.5" Pitch

Replaces:
Intralox 1800 FT

*Non-headed Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
2.5"	.75"	4"	.312"	0%	Yes	No
63.5mm	19.1mm	102mm	7.9mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature		Belt Weight Lb/Ft ²	Colors
		Straight Lb/Ft	Curved Lb/Ft	Fahrenheit Min	Fahrenheit Max		
PP	PP	1200	-	33°	230°	2.00	W, G, B
PE	PE	710	-	-76°	140°	2.25	N, B
Acetal	PE	1490	-	-40°	176°	3.34	N, DB
Ultra Tuff™	POM	1386	-	30°	302°	3.36	N, W, DB
Ultra Tuff XMD™	POM	1386	-	30°	302°	3.70	RB

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN



# of Teeth	PD	Bore Size
6	5"	1.5" s
8	6.5"	1.5", 2.5" s
10	8.1"	1.5", 2.5" s
13	10.5"	1.5", 2.5" s

Special Order Sprockets Available



SAFARI Belting Systems, Inc.
Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com