

SF-1800E

Heavy Duty Groove Top

Paso 2.5"

Reemplazo:
Uni XLB M2 V8

*Capped cabeza



Paso	Espesor	Ancho Mínimo	Perno	Área Abierta	Empujadores	Guardas Laterales
2.5"	1"	8"	.393"	0%	PUSHER	No
63.5mm	25mm	200mm	10mm			

Material de la Banda	Material Estándar del Perno	Resistencia de la Banda		Rango de Temperatura Celsius		Peso de la Banda Lb/Ft ²	Colores
		Recta Lb/Ft	Curved Lb/Ft	Min	Max		
Acetal	PA	6719	-	-46°	66°	6.82	BK
Acetal + AS	PA	6719	-	-46°	66°	6.82	BK
ULT	ULT	6719	-	-1°	150°	6.82	BK

SS Rods Available

# de Dientes	Diámetro de Paso	Medida del Barreno
13 2R	10.43"	2.5" S

Sprockets especiales disponibles sobre pedido

Alteración estándar de la banda	N/A
Sangría estándar de la Empujadores	N/A

BW = Ancho de la Banda, W-Blanco, B-Azul, DB-Azul Oscuro, RB-Azul Real, N-Natural, G-Gris, BK-Negro, BR-Café



SAFARI Belting Systems, Inc.
Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com