

SF-1800B

Heavy Duty Perforated Flat Top Paso 2.5"

Reemplazo:
Uni XLB M2 15%

*Capped cabeza



Paso	Espesor	Ancho Mínimo	Perno	Área Abierta	Empujadores	Guardas Laterales
2.5"	1"	8"	.393"	10%	PUSHER	No
63.5mm	25mm	200mm	10mm			

Material de la Banda	Material Estándar del Perno	Resistencia de la Banda		Rango de Temperatura Celsius		Peso de la Banda Lb/Ft ²	Colores
		Recta Lb/Ft	Curved Lb/Ft	Min	Max		
Acetal	PA	6719	-	-40°	80°	6.82	W, BK
Acetal + AS	PA	6719	-	-40°	80°	6.82	W, BK

SS Rods Available

BW = Ancho de la Banda, W-Blanco, B-Azul, DB-Azul Oscuro, RB-Azul Real, N-Natural, G-Gris, BK-Negro, BR-Café



# de Dientes	Diámetro de Paso	Medida del Barreno
10	7.7"	2.5"S
13	9.6"	2.5",3",4"S
15	11.5"	3.5"S

Sprockets especiales disponibles sobre pedido

Alteración estándar de la banda	+/- 2.6"
Sangría estándar de la Empujadores	N/A



SAFARI Belting Systems, Inc.

Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com