

SF-2600B

Standard Duty Flush Grid

1" Pitch

Compare To:
UNI OWL


*Capped Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
1"	.433"	5.61"	.177"	44%	No	No
25mm	11mm	142.5mm	4.5mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft ²	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
PP	PP	300	-	33°	230°	.62	W, G, B
PE	POM	240	-	-76°	140°	.49	N, B
Acetal	POM	600	-	-50°	150°	.96	W, B
Nylon	PA	500	-	33°	302°	.79	BR
Nylon+Teflon With SS Rods	PSS	600	-	33°	500°	1.57	BR

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN



# of Teeth	PD	Bore Size
9	2.87"	1.5"
11	3.5"	1.5"
13	4.1"	1.5"
15	4.72"	1.5"

Special Order Sprockets Available

Belt Standard Alterations	+/- 1.1"
Flight Standard Indent	N/A



SAFARI Belting Systems, Inc.

Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com