


# SF-500BHD

## Radius Flush Grid

### 1" Pitch

Replaces:  
Intralox 2400  
Flush Grid (same sprockets)

\*Headed Rods




Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
1"	.5"	6.5"	.2"	36%	Yes	No
25mm	12.7mm	165mm	5mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft <sup>2</sup>	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
PP	PA	1300	230	33°	230°	1.50	W, B, G
PE	POM	1010	225	-76°	140°	1.39	N, B
Acetal	PA	1720	330	-50°	150°	1.75	N, DB
Nylon	POM	1720	330	33°	180°	2.45	BR
Ultra-Tuff™	POM	1700	326	30	302	1.73	N, DB
Ultra-Tuff XMD	POM	1700	326	30	302	1.77	RB

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

**WARNING:** Do not place fingers in or on this belt. Fingers can get trapped in belt openings, resulting in personal injury. This belt has pinch points due to the belt spreading and collapsing as it flexes to follow the conveyor path. Pinch points can trap fingers, hair, or clothing, causing personal injury. Do not wear loose clothing, loose gloves, or hand/finger jewelry when working near this belt. Call Customer Service for tags, flyers, and stickers containing this warning.



# of Teeth	PD	Bore Size
12	3.9"	1"R, 1.5"S
18	5.8"	1"R, 1.5"S
24	7.9"	1.5", 2.5"S
12-2R	3.9"	1"R, 1.5"S
15-2R	4.9"	1"R, 1.5"S
18-2R	5.8"	1.5", 2.5"S
21-2R	6.8"	1.5"S
24-2R	7.9"	1.5", 2.5"S

Special Order Sprockets Available

Belt Standard Alterations	+/- .8"
Flight Standard Indent	+/- 1.1" (Depends on Material)



**SAFARI** Belting Systems, Inc.

Conveying Innovation to Industry

220 N Mahaffie Street, Olathe, KS 66061, USA | 913-254-7582 | info@safaribelting.com | SafariBelting.com