

# SF-400RAM

Angled Roller Top

2" Pitch

Replaces:  
Intralox S400ARB

\*Non-Headed Rods



Pitch	Thickness	Min Width	Rod	Open Area	Flights	Side Guards
2"	.625"	6"	.24"	10%	No	No
50.8mm	15.9mm	152mm	6.1mm			

Belt Material	Standard Rod Material	Belt Strength		Temperature Fahrenheit		Belt Weight Lb/Ft <sup>2</sup>	Colors
		Straight Lb/Ft	Curved Lb/Ft	Min	Max		
POM	ULT	1720	-	-50°	150°	3.8	B, W

BW = Belt Width, W-WHITE, B-BLUE, DB-DARK BLUE, RB-ROYAL BLUE, N-NATURAL, G-GRAY, BK-BLACK, BR-BROWN

# of Teeth	PD	Bore Size
6T	4.0"	1.5"S
8T-Split	5.2"	1.5"S
10T-Split	6.5"	1.5"S, 2.5"S
12T-Split	7.7"	1.5"S, 2.5"S
16T-Split	10.3"	1.5"S, 2.5"S

Special Order Sprockets Available

Belt Standard Alterations	(+/-) 2"
Roller Angle	(+/-) 90°



**SAFARI** Belting Systems, Inc.

Conveying Innovation to Industry